

Hamlet

BARCODE SCANNER

FOR LINEAR & QR CODES
USB CABLE 2M

PROFESSIONAL
2D
USB CABLE

HBCS2D100U



DISPLAY CODE

PROFESSIONAL

Hamlet HBCS2D100U è un lettore di codici 2D professionale ideale per il punto vendita, la linea di produzione e la logistica. La tecnologia di scansione 2D imaging ad alta precisione offre ottime prestazioni di lettura sia per i codici a barre lineari che per i codici QR. La tecnologia di scansione 2D Area Imager offre ottime prestazioni di lettura per i codici QR e barcode lineari come EAN e UPC. **La tecnologia con sensore Area Imager consente inoltre la lettura di codici visualizzati su schermi LCD come monitor, smartphone, tablet e computer.** La leggerezza e il design ergonomico permettono un utilizzo prolungato senza fatica. Lo stand in dotazione offre un pratico appoggio per avere sempre lo scanner a portata di mano e può essere utilizzato anche per effettuare scansioni a mani libere. È dotato di cavo USB lungo 2 metri. Realizzato in plastica dura per resistere alle cadute.

LIGHT SOURCES: 617NM LED AIMER, WHITE LED

SUPPORTED SYMBOLOGIES:

1D: CODEBAR, CODE11, CODE39, CODE93, UPC/EAN, CODE128, EAN-128, INTERLEAVED 2 OF 5, MATRIX 2 OF 5, MSI CODE, INDUSTRIAL 2 OF 5, GS1 DATABAR; 2D: QR CODE, DATA MATRIX, PDF417

SCAN TYPE: IMAGE CMOS

SCAN SPEED: >25INCH/63CM PER SECOND

SCAN METHOD: MANUAL/CONTINUOUS/AUTOMATIC INDUCTIVE

SCAN ANGLE: YAW $\pm 60^\circ$, ROTATION 360° , PITCH $\pm 65^\circ$

PRECISION: SR: CODE 39 4.8 MIL, UPC60% 5 MIL, PDF417 5 MIL, DATAMATRIX 7.5 MIL

DEPTH OF SCAN FIELD: 5-390 MM

ERROR RATE: LESS THAN 1/5 MILLION

INDICATOR: LED, BUZZER

INTERFACE: USB-HID, USB-COM, RS232 (ONLY USB CABLE INCLUDED)

COMPATIBLE WITH WINDOWS, MAC, LINUX, ANDROID

DIMENSIONS: 70 X 75 X 173 MM - WEIGHT: 215 G

MATERIAL: ABS + PC - CABLE LENGTH: 2 M

OPERATING TEMPERATURE: $-20^\circ\text{C} \sim 60^\circ\text{C}$

STORAGE TEMPERATURE: $-40^\circ\text{C} \sim 70^\circ\text{C}$

RELATIVE HUMIDITY: 5%~95% (NON-CONDENSING)

DROP/SHOCK RESISTANCE: WITHSTANDS MULTIPLE DROPS

VOLTAGE: DC 5V $\pm 5\%$

CURRENT: 135 MA (OPERATING)



CONTENUTO DELLA SCATOLA

- Barcode Scanner 2D Professionale USB
- Cavo USB/RJ45 (2 m)
- Base di supporto
- Manuale d'uso

hamletcom.com